

11/19 series



- Top plate fixing.
- Double ball bearing swivel head.
- Swivel castors conform to ISO 2184, Class 1.
- Matching fixed castors (100, 125mm).



whl dia	fitted height	swivel radius	tread width	wheel		load capacity	plain bore wheel			roller bearing wheel		
				centre	tyre		swivel	fixed	rep wheel	swivel	fixed	rep wheel
75	108	70	25	nylon		125	3-11-NY		WNY-3M12			
			32	nylon	blue rubber	90	3-11-RN		WRN-3M12			
100	128	85	35	polypropylene		125	4-11-ED	4-19-ED	WED-41M12	4-11-EDB	4-19-EDB	WED-41RBM12
			35	polypropylene	grey cushion rubber	70	4-11-PSW	4-19-PSW	WPS-41WM12	4-11-PSBW	4-19-PSBW	WPS-41RBWM12
			35	polypropylene	black cushion rubber	70	4-11-PS	4-19-PS	WPS-41M12	4-11-PSB	4-19-PSB	WPS-41RBM12
			35	nylon	polyurethane	150				4-11-PNB	4-19-PNB	WPN-41RBM12
125	155	98	35	polypropylene		125	5-11-ED	5-19-ED	WED-51M12	5-11-EDB	5-19-EDB	WED-51RBM12
			35	polypropylene	grey cushion rubber	90	5-11-PSW	5-19-PSW	WPS-51WM12	5-11-PSBW	5-19-PSBW	WPS-51RBWM12
			35	polypropylene	black cushion rubber	90	5-11-PS	5-19-PS	WPS-51M12	5-11-PSB	5-19-PSB	WPS-51RBM12
			35	pressed steel	black cushion rubber	125				5-11-BSB	5-19-BSB	WBS-51RBM12
			35	nylon	polyurethane	150				5-11-PNB	5-19-PNB	WPN-51RBM12



Standard fixings

311
411
511

- = 96 x 78mm
- = 80 x 60mm
- = 76 x 44.5mm
- ⊥ = M8

419
519

- = 105 x 86mm
- = 80 x 60mm
- = 76 x 44.5mm
- ⊥ = M8

Adaptions

Swivel & Wheel Brake

Foot operated pedal brakes both the swivel head and wheel

Available on 100 and 125mm 11 series swivel castors

NOTE: Swivel radius is increased to 122mm

To order add suffix 'SWB' to castor code

Footbrake (as illustrated on page 13)

Foot operated pedal brakes the wheel

Available on 100 and 125mm 11 series swivel castors

NOTE: Swivel radius is increased to 105mm

To order add suffix 'BR' to castor code

Threadguards

Prevent threads, string etc from jamming the wheel

Available on 100 & 125mm 11/19 series castors, except those fitted with BSB wheels

To order add suffix 'G' to castor code



- Single hole fixing.
- Double ball bearing swivel head.

5-11-PSBWBH10

whl dia	fitted height	swivel radius	tread width	wheel		load capacity	plain bore wheel		roller bearing wheel	
				centre	tyre		swivel	rep wheel	swivel	rep wheel
75	105	70	25	nylon		125	3-11-NYBH10	WNY-3M12		
			32	nylon	blue rubber	90	3-11-RNBH10	WRN-3M12		
100	125	85	35	polypropylene		125	4-11-EDBH10	WED-41M12	4-11-EDBBH10	WED-41RBM12
			35	polypropylene	grey cushion rubber	70	4-11-PSWBH10	WPS-41WM12	4-11-PSBWBH10	WPS-41RBWM12
			35	polypropylene	black cushion rubber	70	4-11-PSBH10	WPS-41M12	4-11-PSBBH10	WPS-41RBM12
			35	nylon	polyurethane	150			4-11-PNBBH10	WPN-41RBM12
125	152	98	35	polypropylene		125	5-11-EDBH10	WED-51M12	5-11-EDBBH10	WED-51RBM12
			35	polypropylene	grey cushion rubber	90	5-11-PSWBH10	WPS-51WM12	5-11-PSBWBH10	WPS-51RBWM12
			35	polypropylene	black cushion rubber	90	5-11-PSBH10	WPS-51M12	5-11-PSBBH10	WPS-51RBM12
			35	pressed steel	black cushion rubber	125			5-11-BSBBH10	WBS-51RBM12
			35	nylon	polyurethane	150			5-11-PNBBH10	WPN-51RBM12



Standard fixings



Adaptions

Footbrake
Foot operated pedal brakes the wheel
Available on 100 and 125mm 11 series swivel castors
NOTE: Swivel radius is increased to 105mm
To order add suffix 'BR' to castor code

Swivel & Wheel Brake (as illustrated on page 12)
Foot operated pedal brakes both the swivel head and wheel
Available on 100 and 125mm 11 series swivel castors
NOTE: Swivel radius is increased to 122mm
To order add suffix 'SWB' to castor code

Threadguards
Prevent threads, string etc from jamming the wheel
Available on 100 & 125mm 11 series castors, except those fitted with BSB wheels
To order add suffix 'G' to castor code

11EXP series




5-11-PSBWEXP19

- Expanding adaptor fixing.
- Double ball bearing swivel head.

whl dia	fitted height	swivel radius	tread width	wheel		load capacity	plain bore wheel		roller bearing wheel	
				centre	tyre		swivel	rep wheel	swivel	rep wheel
75	108	70	25	nylon		125	3-11-NYEX	WNY-3M12		
			32	nylon	blue rubber	90	3-11-RNEX	WRN-3M12		
100	128	85	35	polypropylene		125	4-11-EDEX	WED-41M12	4-11-EDBEX	WED-41RBM12
			35	polypropylene	grey cushion rubber	70	4-11-PSWEX	WPS-41WM12	4-11-PSBWEX	WPS-41RBWM12
			35	polypropylene	black cushion rubber	70	4-11-PSEX	WPS-41M12	4-11-PSBEX	WPS-41RBM12
			35	nylon	polyurethane	150			4-11-PNBEX	WPN-41RBM12
125	155	98	35	polypropylene		125	5-11-EDEX	WED-51M12	5-11-EDBEX	WED-51RBM12
			35	polypropylene	grey cushion rubber	90	5-11-PSWEX	WPS-51WM12	5-11-PSBWEX	WPS-51RBWM12
			35	polypropylene	black cushion rubber	90	5-11-PSEX	WPS-51M12	5-11-PSBEX	WPS-51RBM12
			35	pressed steel	black cushion rubber	125			5-11-BSBEX	WBS-51RBM12
			35	nylon	polyurethane	150			5-11-PNBEX	WPN-51RBM12

Standard fixings



Expanding Adaptors

The range of expanders have been designed for use with round or square mild steel tubing. To order add suffix, shown in table below, to castor code.

tube shape	effective range (mm)	colour	reference
○	19.0 - 20.3	white	P19
○	21.8 - 24.5	grey	P22
○	25.0 - 28.5	black	P25
□	19.0 - 20.3	white	S19
□	21.8 - 24.5	grey	S22
□	25.0 - 28.5	black	S25

Please note:

1. If expanding adaptors are being used with any material other than mild steel please ask for advice.
2. Square adaptors are not recommended for mild steel 18 gauge tubing.

Adaptions

Footbrake

(as illustrated on page 13)

Foot operated pedal brakes the wheel

Available on 100 and 125mm 11 series swivel castors
NOTE: Swivel radius is increased to 105mm

To order add suffix 'BR' to castor code

Swivel & Wheel Brake

(as illustrated on page 12)

Foot operated pedal brakes both the swivel head and wheel

Available on 100 and 125mm 11 series swivel castors
NOTE: Swivel radius is increased to 122mm

To order add suffix 'SWB' to castor code

Threadguards

Prevent threads, string etc from jamming the wheel

Available on 100 & 125mm 11 series castors, except those fitted with BSB wheels

To order add suffix 'G' to castor code