


- From the **Pressed steel castors** range
- Double ball race swivel head
- Top plate or bolt hole fixing


**11SOV**  
19SOV

**11SOV + Polyurethane tyred wheel with nylon centre - plate fixing**



| wheel diameter | tread width | fitted height | swivel offset | load capacity | bearing type | fixing type       |                   |                           |
|----------------|-------------|---------------|---------------|---------------|--------------|-------------------|-------------------|---------------------------|
|                |             |               |               |               |              | swivel            | fixed             | swivel + total stop brake |
| <b>100</b>     | 35          | 128           | 32            | 150           | roller       | <b>411SOV PNB</b> | <b>419SOV PNB</b> | <b>411SOV PNB SWB</b>     |
| <b>125</b>     | 35          | 152           | 47.5          | 150           | ball         | <b>511SOV PNB</b> | <b>519SOV PNB</b> | <b>511SOV PNB SWB</b>     |

**11SOV + Polyurethane tyred wheel with nylon centre - bolt hole fixing**



| wheel diameter | tread width | fitted height | swivel offset | load capacity | bearing type | fixing type            |       |                            |
|----------------|-------------|---------------|---------------|---------------|--------------|------------------------|-------|----------------------------|
|                |             |               |               |               |              | swivel                 | fixed | swivel + total stop brake  |
| <b>100</b>     | 35          | 128           | 32            | 150           | roller       | <b>411SOV PNB BH10</b> |       | <b>411SOV PNB BH10 SWB</b> |
| <b>125</b>     | 35          | 152           | 47.5          | 150           | ball         | <b>511SOV PNB BH10</b> |       | <b>511SOV PNB BH10 SWB</b> |



EXPANDING ADAPTOR for round or square tubing  
To suit all bolt hole fixing castors. See page 13

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated



- From the **Pressed steel castors** range
- Suitable for use with V30B, 11SOV and V40A series castors with bolt hole fixing

# EXC

## Round expander sets



| expansion range: min/max | for castors with 10mm bolt hole | for castors with 12mm bolt hole |
|--------------------------|---------------------------------|---------------------------------|
| 19 - 22                  | <b>EXC10 R1922</b>              | <b>EXC12 R1922</b>              |
| 22 - 25                  | <b>EXC10 R2225</b>              | <b>EXC12 R2225</b>              |
| 27 - 30                  | <b>EXC10 R2730</b>              | <b>EXC12 R2730</b>              |

A ring spanner may be required to access head of bolt when tightening

## Square expander sets



| expansion range: min/max | for castors with 10mm bolt hole | for castors with 12mm bolt hole |
|--------------------------|---------------------------------|---------------------------------|
| 19 - 22                  | <b>EXC10 S1922</b>              | <b>EXC12 S1922</b>              |
| 22 - 25                  | <b>EXC10 S2225</b>              | <b>EXC12 S2225</b>              |
| 27 - 30                  | <b>EXC10 S2730</b>              | <b>EXC12 S2730</b>              |

A ring spanner may be required to access head of bolt when tightening

*NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated*