

22/29 series



- Top plate fixing (single hole option - 100, 125mm).
- Double ball bearing swivel head.
- Swivel castors conform to ISO 2184, Class 2 (100, 125mm) & Class 3 (150, 200mm).
- Matching fixed castors.



whl dia	fitted height	swivel radius	tread width	wheel		load capacity	plain bore wheel			roller bearing wheel			ball bearing wheel		
				centre	tyre		swivel	fixed	rep wheel	swivel	fixed	rep wheel	swivel	fixed	rep wheel
100	128	90	32	nylon		250	4-22-NY	4-29-NY	WNY-4M15	4-22-NYB	4-29-NYB	WNY-4RBM15			
			38	nylon	blue rubber	160	4-22-RN	4-29-RN	WRN-4M15	4-22-RNB	4-29-RNB	WRN-4RBM15			
			35	nylon	polyurethane	250	4-22-PN	4-29-PN	WPN-4M15	4-22-PNB	4-29-PNB	WPN-4RBM15			
			38	phenolic		250	4-22-AN	4-29-AN	WAN-4M15	4-22-ANB	4-29-ANB	WAN-4RB			
125	155	105	35	nylon		250	5-22-NY	5-29-NY	WNY-5M15	5-22-NYB	5-29-NYB	WNY-5RBM15			
			38	nylon	blue rubber	180	5-22-RN	5-29-RN	WRN-5M15	5-22-RNB	5-29-RNB	WRN-5RBM15			
			35	nylon	polyurethane	250	5-22-PN	5-29-PN	WPN-5M15	5-22-PNB	5-29-PNB	WPN-5RBM15			
			38	phenolic		250	5-22-AN	5-29-AN	WAN-5M15	5-22-ANB	5-29-ANB	WAN-5RB			
			38	cast iron	black rubber	180	5-22-RT	5-29-RT	WRT-M15	5-22-RTB	5-29-RTB	WRT-5RBM15			
150	188	128	38	polypropylene	black cushion rubber	135	6-22-PS	6-29-PS	WPS-6M20	6-22-PSB	6-29-PSB	WPS-6RBM20			
			38	nylon		500	6-22-NY	6-29-NY	WNY-6M20	6-22-NYB	6-29-NYB	WNY-6RBM20			
			45	nylon	blue rubber	300	6-22-RN	6-29-RN	WRN-6M20	6-22-RNB	6-29-RNB	WRN-6RBM20			
			45	nylon	polyurethane	500	6-22-PN	6-29-PN	WPN-6M20	6-22-PNB	6-29-PNB	WPN-6RBM20	6-22-PNB	6-29-PNB	WPN-6BJM12
			45	cast iron	black rubber	400	6-22-RT	6-29-RT	WRT-6M20	6-22-RTB	6-29-RTB	WRT-6RBM20	6-22-RTB	6-29-RTB	WRT-6BJM12
			45	cast iron	elastic black rubber	400							6-22-CTB	6-29-CTB	WCT-6BJM12
			38	cast iron	polyurethane	500				6-22-SUB	6-29-SUB	WSU-61RBM20			
			45	cast iron	polyurethane	500							6-22-SUB	6-29-SUB	WSU-6BJM12
160	193	133	38	pressed steel	grey cushion rubber	135				6-22-BSBW	6-29-BSBW	WBS-6RBM20			
			38	pressed steel	black cushion rubber	135				6-22-BSB	6-29-BSB	WBS-6RBM20			
200	238	153	50	polypropylene	black cushion rubber	205	8-22-PS	8-29-PS	WPS-8M20	8-22-PSB	8-29-PSB	WPS-8RBM20			
			45	pressed steel	grey cushion rubber	205				8-22-BSBW	8-29-BSBW	WBS-8RBM20			
			45	pressed steel	black cushion rubber	205				8-22-BSB	8-29-BSB	WBS-8RBM20			
			48	pressed steel	grey pneumatic rubber	75				8-22-ATBW	8-29-ATBW	WAT-8RBM20			
			48	pressed steel	black pneumatic rubber	75				8-22-ATB	8-29-ATB	WAT-8RBM20			
			38	nylon		500	8-22-NY	8-29-NY	WNY-8M20	8-22-NYB	8-29-NYB	WNY-8RBM20			
			50	nylon	blue rubber	450	8-22-RN	8-29-RN	WRN-8M20	8-22-RNB	8-29-RNB	WRN-8RBM20			
			50	nylon	polyurethane	500	8-22-PN	8-29-PN	WPN-8M20	8-22-PNB	8-29-PNB	WPN-8RBM20	8-22-PNB	8-29-PNB	WPN-8BJM12
			51	cast iron	black rubber	500	8-22-RT	8-29-RT	WRT-8M20	8-22-RTB	8-29-RTB	WRT-8RBM20	8-22-RTB	8-29-RTB	WRT-8BJM12
			45	cast iron	elastic black rubber	500							8-22-CTB	8-29-CTB	WCT-8BJM12
			51	cast iron	polyurethane	500				8-22-SUB	8-29-SUB	WSU-8RBM20	8-22-SUB	8-29-SUB	WSU-8BJM12

1.2 Pressed Steel Castors



Standard fixings

<p>□ = 105 x 86mm ● = 80 x 60mm ⚙ = M8</p>	<p>□ = 105 x 88mm ● = 80 x 60mm ⚙ = M8</p>	<p>□ = 135 x 110mm ● = 105 x 80mm ● = 105 x 75mm ⚙ = M10</p>	<p>□ = 135 x 115mm ● = 105 x 80mm ● = 105 x 75mm ⚙ = M10</p>

Adaptions

◀ Footbrake
Foot operated pedal brakes the wheel
Available on all 100 & 125mm 22 series swivel castors except those with CI, CIB wheels
To order add suffix **'BR'** to castor code

◀ Swivel & Wheel Brake
Foot operated pedal brakes both the swivel head and wheel
Available on all 22 series castors except those with AN, AT & BS wheels. Not available with V or ST adaptations

NOTE: Swivel radius is increased as follows
422 to 130mm, 522 to 130mm, 622 to 161mm
To order add suffix **'SWB'** to castor code

Single Hole fitting ▶
Available on 100 & 125mm 22 series swivel castors
Fitted height is reduced by 5mm
Load capacity is reduced to a maximum 200kg
To order add suffix **'BH12'** to castor code

Threaded Stem and Nut Fitting
Available on 100mm 22 series castors
Stem is M16 x 30mm
To order add suffix **'ST'** to castor code

Threadguards
Prevent threads, string etc from jamming the wheel
Available on 22/29 series castors fitted with plain bore NY, PN, RN wheels
To order add suffix **'G'** to castor code

Corrosion free wheel tubes
Provide protection in wet conditions
Available on 22/29 series castors fitted with plain bore NY RN PN wheels
To order add suffix **'SS'** to castor code