


2V30A

2V32A




- Pressed steel construction
- Double ball race swivel head
- Top plate or bolt hole fixing
- Forged central pin

VARLEY




2V30A + Nylon wheel - plate fixing



wheel diameter	overall tread width	fitted height	swivel offset	load capacity	bearing type	bearing type			replacement wheel
						swivel	fixed	swivel + total stop brake	
50	37	72	30	60	plain	2V30A 050 NYP P01		2V32A 050 NYP P01	
75	51	97.5	33	90	plain	2V30A 075 NYP P01		2V32A 075 NYP P01	

2V30A + Nylon wheel - bolt hole fixing




wheel diameter	overall tread width	fitted height	swivel offset	load capacity	bearing type	bearing type			replacement wheel
						swivel	fixed	swivel + total stop brake	
50	37	72	30	60	plain	2V30A 050 NYP B10		2V32A 050 NYP B10	
75	51	97.5	33	90	plain	2V30A 075 NYP B10		2V32A 075 NYP B10	

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated




VARLEY



- o Pressed steel construction
- o Double ball race swivel head
- o Top plate or bolt hole fixing
- o Forged central pin


2V30A
2V32A

2V30A + Rubber tyred wheel - plate fixing



wheel diameter	overall tread width	fitted height	swivel offset	load capacity	bearing type	swivel +			replacement wheel
						swivel	fixed	total stop brake	
50	37	72	30	60	plain	2V30A 050 GRP P01		2V32A 050 GRP P01	
75	51	100	33	90	plain	2V30A 075 GRP P01		2V32A 075 GRP P01	

2V30A + Rubber tyred wheel - bolt hole fixing



wheel diameter	overall tread width	fitted height	swivel offset	load capacity	bearing type	swivel +			replacement wheel
						swivel	fixed	total stop brake	
50	37	72	30	60	plain	2V30A 050 GRP B10		2V32A 050 GRP B10	
75	51	100	33	90	plain	2V30A 075 GRP B10		2V32A 075 GRP B10	

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated