



5-91-PNB



5-99-RNB

- Top plate fixing.
- Ball bearing swivel head.
- Swivel castors conform to ISO 2184, Class 3.
- Matching fixed castors.



whl dia	fitted height	swivel radius	tread width	wheel		load capacity	plain bore wheel			roller bearing wheel		
				centre	tyre		swivel	fixed	rep wheel	swivel	fixed	rep wheel
125	154	96	35	nylon		365	5-91-NY	5-99-NY	WNY-5M15	5-91-NYB	5-99-NYB	WNY-5RBM15
			38	nylon	blue rubber	180	5-91-RN	5-99-RN	WRN-5M15	5-91-RNB	5-99-RNB	WRN-5RBM15
			38	cast iron	black rubber	180	5-91-RT	5-99-RT	WRT-5M15	5-91-RTB	5-99-RTB	WRT-5RBM15



Page 31

Standard fixings

591

- = 143 x 102mm
- = 105 x 80mm
- = 116 x 63.5mm
- ⚙ = M10

599

- = 145 x 108mm
- = 105 x 80mm
- = 116 x 63.5mm
- ⚙ = M10

Adaptions

◀ Footbrake
Foot operated pedal brakes the wheel
Available on all 91 series castors
To order add suffix **'BR'** to castor code

◀ Threadguards
Prevent threads, string etc from jamming the wheel
Available on 91/99 series castors fitted with plain bore NY, RN wheels
To order add suffix **'G'** to castor code

Corrosion Free Wheel Tubes
Provide protection in wet conditions
Available on 91/99 series castors fitted with plain bore NY, RN wheels
To order add suffix **'SS'** to castor code