



5-91-PNB



5-99-RNB

- Top plate fixing.
- Ball bearing swivel head.
- Swivel castors conform to ISO 2184, Class 3.
- Matching fixed castors.



whl dia	fitted height	swivel radius	tread width	wheel		load capacity	plain bore wheel			roller bearing wheel		
				centre	tyre		swivel	fixed	rep wheel	swivel	fixed	rep wheel
125	154	96	35	nylon		365	5-91-NY	5-99-NY	WNY-5M15	5-91-NYB	5-99-NYB	WNY-5RBM15
			38	nylon	blue rubber	180	5-91-RN	5-99-RN	WRN-5M15	5-91-RNB	5-99-RNB	WRN-5RBM15
			38	cast iron	black rubber	180	5-91-RT	5-99-RT	WRT-5M15	5-91-RTB	5-99-RTB	WRT-5RBM15



### Standard fixings

591

- = 143 x 102mm
- = 105 x 80mm
- = 116 x 63.5mm
- ⚓ = M10

599

- = 145 x 108mm
- = 105 x 80mm
- = 116 x 63.5mm
- ⚓ = M10

### Adaptions

**◀ Footbrake**  
Foot operated pedal brakes the wheel  
Available on all 91 series castors  
To order add suffix **'BR'** to castor code

**◀ Threadguards**  
Prevent threads, string etc from jamming the wheel  
Available on 91/99 series castors fitted with plain bore NY, RN wheels  
To order add suffix **'G'** to castor code

**Corrosion Free Wheel Tubes**  
Provide protection in wet conditions  
Available on 91/99 series castors fitted with plain bore NY, RN wheels  
To order add suffix **'SS'** to castor code