



CATERING  
**V30B**  
**V32B**  
**EXC EXH AAS**



- Pressed steel construction
- Double ball race swivel head
- Bolt hole fixing
- A range of fittings suitable for use with any bolt hole fixing V30B series castor




**V30B + Nylon wheel – bolt hole fixing**



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total stop brake
<b>100</b>	27	130	38	80	roller	<b>V30B 100 NYR B12</b>		<b>V32B 100 NYR B12</b>
<b>125</b>	27	153	42	100	roller	<b>V30B 125 NYR B12</b>		<b>V32B 125 NYR B12</b>

**V30B + Grey rubber tyred wheel with polypropylene centre – bolt hole fixing**



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total stop brake
<b>100</b>	27	130	38	80	plain	<b>V30B 100 GRP B12 G</b>		<b>V32B 100 GRP B12 G</b>
<b>125</b>	27	153	42	100	plain	<b>V30B 125 GRP B12 G</b>		<b>V32B 125 GRP B12 G</b>

**EXC expander sets**



**EXH heavy duty square expander sets**




Expander suits tube size of 30mm square x 1.2-1.5 guage

90mm length is designed to ensure even expansion, extra rigidity and reliability

Order ref **EXH12 S2728**

expansion range	round	square
19 - 22	<b>EXC12 R1922</b>	<b>EXC12 S1922</b>
22 - 25	<b>EXC12 R2225</b>	<b>EXC12 S2225</b>
27 - 30	<b>EXC12 R2730</b>	<b>EXC12 S2730</b>

**AAS American specification threaded pin**



Order ref **V30B AAS**

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated