

Cast Iron Single Flanged

- Centre: Cast iron.
- Tyre: n/a
- Finish: Black.



CSF200/40/BJM25

tread dia	tread width	overall dia	flange width	hub width	bore dia	load cap §	plain bore	plain + keyway	ball bearing
							ref	ref	ref
75	25	100	12	37	20	225	CSF75/25/PBM 20	CSF75/25/KM 20	CSF75/25/BJM 20
					25	225	CSF75/25/PBM 25	CSF75/25/KM 25	CSF75/25/BJM 25
					30	225	CSF75/25/PBM 30	CSF75/25/KM 30	
					3/4"	225	CSF75/25/PBI 0.75	CSF75/25/KI 0.75	CSF75/25/BJI 0.75
					1"	225	CSF75/25/PBI 1.00	CSF75/25/KI 1.00	CSF75/25/BJI 1.00
					1 1/4"	225	CSF75/25/PBI 1.25	CSF75/25/KI 1.25	
100	25	125	12	37	20	300	CSF100/25/PBM 20	CSF100/25/KM 20	CSF100/25/BJM 20
					25	300	CSF100/25/PBM 25	CSF100/25/KM 25	CSF100/25/BJM 25
					30	300	CSF100/25/PBM 30	CSF100/25/KM 30	
					3/4"	300	CSF100/25/PBI 0.75	CSF100/25/KI 0.75	CSF100/25/BJI 0.75
					1"	300	CSF100/25/PBI 1.00	CSF100/25/KI 1.00	CSF100/25/BJI 1.00
					1 1/4"	300	CSF100/25/PBI 1.25	CSF100/25/KI 1.25	
133	35	160	12	47	20	560	CSF133/35/PBM 20	CSF133/35/KM 20	CSF133/35/BJM 20
					25	560	CSF133/35/PBM 25	CSF133/35/KM 25	CSF133/35/BJM 25
					30	560	CSF133/35/PBM 30	CSF133/35/KM 30	CSF133/35/BJM 30
					35	560	CSF133/35/PBM 35	CSF133/35/KM 35	
					3/4"	560	CSF133/35/PBI 0.75	CSF133/35/KI 0.75	CSF133/35/BJI 0.75
					1"	560	CSF133/35/PBI 1.00	CSF133/35/KI 1.00	CSF133/35/BJI 1.00
150	40	185	12	52	25	720	CSF150/40/PBM 25	CSF150/40/KM 25	CSF150/40/BJM 25
					30	720	CSF150/40/PBM 30	CSF150/40/KM 30	CSF150/40/BJM 30
					35	720	CSF150/40/PBM 35	CSF150/40/KM 35	
					3/4"	720	CSF150/40/PBI 0.75	CSF150/40/KI 0.75	
					1"	720	CSF150/40/PBI 1.00	CSF150/40/KI 1.00	CSF150/40/BJI 1.00
					1 1/4"	720	CSF150/40/PBI 1.25	CSF150/40/KI 1.25	CSF150/40/BJI 1.25
200	40	235	12	52	25	960	CSF200/40/PBM 25	CSF200/40/KM 25	CSF200/40/BJM 25
					30	960	CSF200/40/PBM 30	CSF200/40/KM 30	CSF200/40/BJM 30
					35	960	CSF200/40/PBM 35	CSF200/40/KM 35	
					1 1/4"	960	CSF200/40/PBI 1.25	CSF200/40/KI 1.25	CSF200/40/BJI 1.25
					1 1/2"	960	CSF200/40/PBI 1.50	CSF200/40/KI 1.50	CSF200/40/BJI 1.50
					2"	960	CSF200/40/PBI 2.00	CSF200/40/KI 2.00	
225	55	260	15	70	30	1485	CSF225/55/PBM 30	CSF225/55/KM 30	CSF225/55/BJM 30
					35	1485	CSF225/55/PBM 35	CSF225/55/KM 35	CSF225/55/BJM 35
					40	1485	CSF225/55/PBM 40	CSF225/55/KM 40	
					50	1485	CSF225/55/PBM 50	CSF225/55/KM 50	
					1 1/4"	1485	CSF225/55/PBI 1.25	CSF225/55/KI 1.25	CSF225/55/BJI 1.25
					1 1/2"	1485	CSF225/55/PBI 1.50	CSF225/55/KI 1.50	CSF225/55/BJI 1.50
250	50	285	15	65	30	1500	CSF250/50/PBM 30	CSF250/50/KM 30	CSF250/50/BJM 30
					35	1500	CSF250/50/PBM 35	CSF250/50/KM 35	CSF250/50/BJM 35
					40	1500	CSF250/50/PBM 40	CSF250/50/KM 40	
					50	1500	CSF250/50/PBM 50	CSF250/50/KM 50	
					1 1/4"	1500	CSF250/50/PBI 1.25	CSF250/50/KI 1.25	CSF250/50/BJI 1.25
					1 1/2"	1500	CSF250/50/PBI 1.50	CSF250/50/KI 1.50	CSF250/50/BJI 1.50
300	60	345	20	80	35	2160	CSF300/60/PBM 35	CSF300/60/KM 35	CSF300/60/BJM 35
					40	2160	CSF300/60/PBM 40	CSF300/60/KM 40	CSF300/60/BJM 40
					50	2160	CSF300/60/PBM 50	CSF300/60/KM 50	
					1 1/4"	2160	CSF300/60/PBI 1.25	CSF300/60/KI 1.25	CSF300/60/BJI 1.25
					1 1/2"	2160	CSF300/60/PBI 1.50	CSF300/60/KI 1.50	CSF300/60/BJI 1.50
					2"	2160	CSF300/60/PBI 2.00	CSF300/60/KI 2.00	

§ = Load capacity mentioned is maximum load, ie. when the full tread width is in contact with the rail.

Standard machining includes 3° taper tread and parallel flange.

Keyways are parallel and to BS46 Part 1 1958.

Axles are available to suit these wheels, details upon request.