


# HIGH TEMPERATURE M20HT


continued on next page



- Effective range: -40°C to +270°C
- High temperature grease and swivel seal



## M20HT + Thermoplastic wheel - plate fixing



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total stop brake
<b>80</b>	30	106	33	120	plain	<b>28402</b>	<b>28502</b>	
<b>100</b>	30	128	37	120	plain	<b>28406</b>	<b>28506</b>	
<b>125</b>	35	160	49	170	plain	<b>28409</b>	<b>28509</b>	

## M20HT + Thermoplastic wheel - bolt hole fixing



Castors with **GA** suffix


M10

M12 BOLT HOLE is also available.  
Replace **GA** with **GB** in castor code.

Castors with **GC** suffix

M12

M14 BOLT HOLE is also available.  
Replace **GC** with **GD** in castor code.



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total stop brake
<b>80</b>	30	106	33	120	plain	<b>28602GA</b>		
<b>100</b>	30	128	37	120	plain	<b>28606GA</b>		
<b>125</b>	35	160	49	200	plain	<b>28610GC</b>		

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated