




**Plastic Rollers / Round  
Spring Loaded Steel Spindles**

Ideal for use in light duty, general purpose conveyors.

Roller material: **Plastic**  
Spindle material: **Steel**  
Spindle type: **Round, spring loaded**




Roller dia. (mm)	Wall gauge (mm)	Roller length (mm)	Inside frame width (mm)	Load cap. (kg)	Spindle dia. A (mm)	Order code
20	1.5	100	105	2.5	5	R20 PL 100 TR05
20	1.5	200	205	2.5	5	R20 PL 200 TR05
20	1.5	300	305	2.5	5	R20 PL 300 TR05
20	1.5	400	405	0.5	5	R20 PL 400 TR05
40	2.5	200	210	7	8	R40 PL 200 TR08
40	2.5	200	210	7	10	R40 PL 200 TR10
40	2.5	300	310	7	8	R40 PL 300 TR08
40	2.5	300	310	7	10	R40 PL 300 TR10
40	2.5	400	410	7	8	R40 PL 400 TR08
40	2.5	400	410	7	10	R40 PL 400 TR10
40	2.5	500	510	7	8	R40 PL 500 TR08
40	2.5	500	510	7	10	R40 PL 500 TR10
40	2.5	600	610	1	8	R40 PL 600 TR08
40	2.5	600	610	1	10	R40 PL 600 TR10
50	3	300	310	10	8	R50 PL 300 TR08
50	3	300	310	10	10	R50 PL 300 TR10
50	3	400	410	10	8	R50 PL 400 TR08
50	3	400	410	10	10	R50 PL 400 TR10
50	3	500	510	10	8	R50 PL 500 TR08
50	3	500	510	10	10	R50 PL 500 TR10
50	3	600	610	10	8	R50 PL 600 TR08
50	3	600	610	10	10	R50 PL 600 TR10
50	3	700	710	5	8	R50 PL 700 TR08
50	3	700	710	5	10	R50 PL 700 TR10

**Plastic Rollers / Round  
Spring Loaded Stainless Steel Spindles**

Ideal for use in light duty, general purpose conveyors. Also suitable for use in humid conditions and in the food industry in conjunction with stainless steel components.

Roller material: **Plastic**  
Spindle material: **Stainless steel**  
Spindle type: **Round, spring loaded**




**STAINLESS  
spindles**

Roller dia. (mm)	Wall gauge (mm)	Roller length (mm)	Inside frame width (mm)	Load cap. (kg)	Spindle dia. A (mm)	Order code
20	1.5	100	105	2.5	5	R20 PL 100 SR05
20	1.5	200	205	2.5	5	R20 PL 200 SR05
20	1.5	300	305	2.5	5	R20 PL 300 SR05
20	1.5	400	405	0.5	5	R20 PL 400 SR05
40	2.5	200	210	7	8	R40 PL 200 SR08
40	2.5	200	210	7	10	R40 PL 200 SR10
40	2.5	300	310	7	8	R40 PL 300 SR08
40	2.5	300	310	7	10	R40 PL 300 SR10
40	2.5	400	410	7	8	R40 PL 400 SR08
40	2.5	400	410	7	10	R40 PL 400 SR10
40	2.5	500	510	7	8	R40 PL 500 SR08
40	2.5	500	510	7	10	R40 PL 500 SR10
40	2.5	600	610	1	8	R40 PL 600 SR08
40	2.5	600	610	1	10	R40 PL 600 SR10
50	3	300	310	10	8	R50 PL 300 SR08
50	3	300	310	10	10	R50 PL 300 SR10
50	3	400	410	10	8	R50 PL 400 SR08
50	3	400	410	10	10	R50 PL 400 SR10
50	3	500	510	10	8	R50 PL 500 SR08
50	3	500	510	10	10	R50 PL 500 SR10
50	3	600	610	10	8	R50 PL 600 SR08
50	3	600	610	10	10	R50 PL 600 SR10
50	3	700	710	5	8	R50 PL 700 SR08
50	3	700	710	5	10	R50 PL 700 SR10

**Plastic Rollers / Hexagonal  
Spring Loaded Steel Spindles**

Ideal for use in light duty, general purpose conveyors.

Roller material: **Plastic**  
Spindle material: **Steel**  
Spindle type: **Hexagonal, spring loaded**




Roller dia. (mm)	Wall gauge (mm)	Roller length (mm)	Inside frame width (mm)	Load cap. (kg)	Spindle dia. A (mm)	Order code
40	2	200	210	99	11	R40 PL 200 TH11
40	2	300	310	99	11	R40 PL 300 TH11
40	2	400	410	99	11	R40 PL 400 TH11
40	2	500	510	99	11	R40 PL 500 TH11
40	2	600	610	99	11	R40 PL 600 TH11
50	3	300	310	99	11	R50 PL 300 TH11
50	3	400	410	99	11	R50 PL 400 TH11
50	3	500	510	99	11	R50 PL 500 TH11
50	3	600	610	99	11	R50 PL 600 TH11
50	3	700	710	99	11	R50 PL 700 TH11

**Plastic Rollers / Hexagonal  
Spring Loaded Stainless Steel Spindles**

Ideal for use in light duty, general purpose conveyors. Also suitable for use in humid conditions and in the food industry in conjunction with stainless steel components.

Roller material: **Plastic**  
Spindle material: **Stainless steel**  
Spindle type: **Hexagonal, spring loaded**



**STAINLESS  
spindles**

Roller dia. (mm)	Wall gauge (mm)	Roller length (mm)	Inside frame width (mm)	Load cap. (kg)	Spindle dia. A (mm)	Order code
40	2	200	210	99	11	R40 PL 200 SH11
40	2	300	310	99	11	R40 PL 300 SH11
40	2	400	410	99	11	R40 PL 400 SH11
40	2	500	510	99	11	R40 PL 500 SH11
40	2	600	610	99	11	R40 PL 600 SH11
50	3	300	310	99	11	R40 PL 300 SH11
50	3	400	410	99	11	R40 PL 400 SH11
50	3	500	510	99	11	R40 PL 500 SH11
50	3	600	610	99	11	R40 PL 600 SH11
50	3	700	710	99	11	R40 PL 700 SH11

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated