




**Steel Rollers /
Round Spring Loaded Spindles**

Ideal for use in medium duty, general purpose conveyors.

Roller material: **Steel**
Spindle material: **Steel**
Spindle type: **Round, spring loaded**




| Roller dia. (mm) | Wall gauge (mm) | Roller length (mm) | Inside frame width (mm) | Load cap. (kg) | Spindle dia. A (mm) | Order code |
|------------------|-----------------|--------------------|-------------------------|----------------|---------------------|------------------|
| 25 | 1.2 | 100 | 105 | 10 | 6 | R25 ST 100 TR06 |
| 25 | 1.2 | 150 | 155 | 10 | 6 | R25 ST 150 TR06 |
| 25 | 1.2 | 200 | 205 | 10 | 6 | R25 ST 200 TR06 |
| 25 | 1.2 | 250 | 255 | 10 | 6 | R25 ST 250 TR06 |
| 25 | 1.2 | 300 | 305 | 10 | 6 | R25 ST 300 TR06 |
| 25 | 1.2 | 350 | 355 | 10 | 6 | R25 ST 350 TR06 |
| 25 | 1.2 | 400 | 405 | 10 | 6 | R25 ST 400 TR06 |
| 25 | 1.2 | 450 | 455 | 10 | 6 | R25 ST 450 TR06 |
| 25 | 1.2 | 500 | 505 | 10 | 6 | R25 ST 500 TR06 |
| 40 | 1.5 | 200 | 210 | 25 | 8 | R40 ST 200 TR08 |
| 40 | 1.5 | 200 | 210 | 25 | 10 | R40 ST 200 TR10 |
| 40 | 1.5 | 250 | 260 | 25 | 8 | R40 ST 250 TR08 |
| 40 | 1.5 | 250 | 260 | 25 | 10 | R40 ST 250 TR10 |
| 40 | 1.5 | 300 | 310 | 25 | 8 | R40 ST 300 TR08 |
| 40 | 1.5 | 300 | 310 | 25 | 10 | R40 ST 300 TR10 |
| 40 | 1.5 | 350 | 360 | 25 | 8 | R40 ST 350 TR08 |
| 40 | 1.5 | 350 | 360 | 25 | 10 | R40 ST 350 TR10 |
| 40 | 1.5 | 400 | 410 | 25 | 8 | R40 ST 400 TR08 |
| 40 | 1.5 | 400 | 410 | 25 | 10 | R40 ST 400 TR10 |
| 40 | 1.5 | 450 | 460 | 25 | 8 | R40 ST 450 TR08 |
| 40 | 1.5 | 450 | 460 | 25 | 10 | R40 ST 450 TR10 |
| 40 | 1.5 | 500 | 510 | 25 | 8 | R40 ST 500 TR08 |
| 40 | 1.5 | 500 | 510 | 25 | 10 | R40 ST 500 TR10 |
| 40 | 1.5 | 550 | 560 | 25 | 8 | R40 ST 550 TR08 |
| 40 | 1.5 | 550 | 560 | 25 | 10 | R40 ST 550 TR10 |
| 40 | 1.5 | 600 | 610 | 25 | 8 | R40 ST 600 TR08 |
| 40 | 1.5 | 600 | 610 | 25 | 10 | R40 ST 600 TR10 |
| 50 | 1.5 | 300 | 310 | 120 | 10 | R50 ST 300 TR10 |
| 50 | 1.5 | 300 | 310 | 120 | 12 | R50 ST 300 TR12 |
| 50 | 1.5 | 350 | 360 | 120 | 10 | R50 ST 350 TR10 |
| 50 | 1.5 | 350 | 360 | 120 | 12 | R50 ST 350 TR12 |
| 50 | 1.5 | 400 | 410 | 120 | 10 | R50 ST 400 TR10 |
| 50 | 1.5 | 400 | 410 | 120 | 12 | R50 ST 400 TR12 |
| 50 | 1.5 | 450 | 460 | 120 | 10 | R50 ST 450 TR10 |
| 50 | 1.5 | 450 | 460 | 120 | 12 | R50 ST 450 TR12 |
| 50 | 1.5 | 500 | 510 | 120 | 10 | R50 ST 500 TR10 |
| 50 | 1.5 | 500 | 510 | 120 | 12 | R50 ST 500 TR12 |
| 50 | 1.5 | 550 | 560 | 120 | 10 | R50 ST 550 TR10 |
| 50 | 1.5 | 550 | 560 | 120 | 12 | R50 ST 550 TR12 |
| 50 | 1.5 | 600 | 610 | 100 | 10 | R50 ST 600 TR10 |
| 50 | 1.5 | 600 | 610 | 100 | 12 | R50 ST 600 TR12 |
| 50 | 1.5 | 650 | 660 | 80 | 10 | R50 ST 650 TR10 |
| 50 | 1.5 | 650 | 660 | 80 | 12 | R50 ST 650 TR12 |
| 50 | 1.5 | 700 | 710 | 70 | 10 | R50 ST 700 TR10 |
| 50 | 1.5 | 700 | 710 | 70 | 12 | R50 ST 700 TR12 |
| 60 | 2 | 500 | 510 | 120 | 10 | R60 ST 500 TR10 |
| 60 | 2 | 500 | 510 | 120 | 12 | R60 ST 500 TR12 |
| 60 | 2 | 550 | 560 | 120 | 10 | R60 ST 550 TR10 |
| 60 | 2 | 550 | 560 | 120 | 12 | R60 ST 550 TR12 |
| 60 | 2 | 600 | 610 | 120 | 10 | R60 ST 600 TR10 |
| 60 | 2 | 600 | 610 | 120 | 12 | R60 ST 600 TR12 |
| 60 | 2 | 650 | 660 | 120 | 10 | R60 ST 650 TR10 |
| 60 | 2 | 650 | 660 | 120 | 12 | R60 ST 650 TR12 |
| 60 | 2 | 700 | 710 | 120 | 10 | R60 ST 700 TR10 |
| 60 | 2 | 700 | 710 | 120 | 12 | R60 ST 700 TR12 |
| 60 | 2 | 750 | 760 | 120 | 10 | R60 ST 750 TR10 |
| 60 | 2 | 750 | 760 | 120 | 12 | R60 ST 750 TR12 |
| 60 | 2 | 800 | 810 | 120 | 10 | R60 ST 800 TR10 |
| 60 | 2 | 800 | 810 | 120 | 12 | R60 ST 800 TR12 |
| 60 | 2 | 850 | 860 | 120 | 10 | R60 ST 850 TR10 |
| 60 | 2 | 850 | 860 | 120 | 12 | R60 ST 850 TR12 |
| 60 | 2 | 900 | 910 | 100 | 10 | R60 ST 900 TR10 |
| 60 | 2 | 900 | 910 | 100 | 12 | R60 ST 900 TR12 |
| 60 | 2 | 950 | 960 | 90 | 10 | R60 ST 950 TR10 |
| 60 | 2 | 950 | 960 | 90 | 12 | R60 ST 950 TR12 |
| 60 | 2 | 1000 | 1010 | 80 | 10 | R60 ST 1000 TR10 |
| 60 | 2 | 1000 | 1010 | 80 | 12 | R60 ST 1000 TR12 |

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated

**Steel Rollers /
Hexagonal Spring Loaded Spindles**

Ideal for use in medium duty, general purpose conveyors.

Roller material: **Steel**
Spindle material: **Steel**
Spindle type: **Hexagonal, spring loaded**




| Roller dia. (mm) | Wall gauge (mm) | Roller length (mm) | Inside frame width (mm) | Load cap. (kg) | Spindle size A (mm) | Order code |
|------------------|-----------------|--------------------|-------------------------|----------------|---------------------|------------------|
| 50 | 1.5 | 300 | 310 | 120 | 11 | R50 ST 300 TH11 |
| 50 | 1.5 | 350 | 360 | 120 | 11 | R50 ST 350 TH11 |
| 50 | 1.5 | 400 | 410 | 120 | 11 | R50 ST 400 TH11 |
| 50 | 1.5 | 450 | 460 | 120 | 11 | R50 ST 450 TH11 |
| 50 | 1.5 | 500 | 510 | 120 | 11 | R50 ST 500 TH11 |
| 50 | 1.5 | 550 | 560 | 120 | 11 | R50 ST 550 TH11 |
| 50 | 1.5 | 600 | 610 | 120 | 11 | R50 ST 600 TH11 |
| 50 | 1.5 | 650 | 660 | 120 | 11 | R50 ST 650 TH11 |
| 50 | 1.5 | 700 | 710 | 120 | 11 | R50 ST 700 TH11 |
| 50 | 1.5 | 750 | 760 | 120 | 11 | R50 ST 750 TH11 |
| 50 | 1.5 | 800 | 810 | 120 | 11 | R50 ST 800 TH11 |
| 60 | 2 | 300 | 310 | 120 | 11 | R60 ST 300 TH11 |
| 60 | 2 | 350 | 360 | 120 | 11 | R60 ST 350 TH11 |
| 60 | 2 | 400 | 410 | 120 | 11 | R60 ST 400 TH11 |
| 60 | 2 | 450 | 460 | 120 | 11 | R60 ST 450 TH11 |
| 60 | 2 | 500 | 510 | 120 | 11 | R60 ST 500 TH11 |
| 60 | 2 | 550 | 560 | 120 | 11 | R60 ST 550 TH11 |
| 60 | 2 | 600 | 610 | 120 | 11 | R60 ST 600 TH11 |
| 60 | 2 | 650 | 660 | 120 | 11 | R60 ST 650 TH11 |
| 60 | 2 | 700 | 710 | 120 | 11 | R60 ST 700 TH11 |
| 60 | 2 | 750 | 760 | 120 | 11 | R60 ST 750 TH11 |
| 60 | 2 | 800 | 810 | 120 | 11 | R60 ST 800 TH11 |
| 60 | 2 | 850 | 860 | 120 | 11 | R60 ST 850 TH11 |
| 60 | 2 | 900 | 910 | 100 | 11 | R60 ST 900 TH11 |
| 60 | 2 | 950 | 960 | 90 | 11 | R60 ST 950 TH11 |
| 60 | 2 | 1000 | 1010 | 80 | 11 | R60 ST 1000 TH11 |

**Steel Rollers /
Female Threaded Spindles**

Ideal for use in medium duty, general purpose conveyors.

Roller material: **Steel**
Spindle material: **Steel**
Spindle type: **Round**



| Roller dia. (mm) | Wall gauge (mm) | Roller length (mm) | Inside frame width (mm) | Load cap. (kg) | Tapped hole A | Order code |
|------------------|-----------------|--------------------|-------------------------|----------------|---------------|------------------|
| 50 | 1.5 | 300 | 310 | 120 | M8 | R50 ST 300 TFM8 |
| 50 | 1.5 | 350 | 360 | 120 | M8 | R50 ST 350 TFM8 |
| 50 | 1.5 | 400 | 410 | 120 | M8 | R50 ST 400 TFM8 |
| 50 | 1.5 | 450 | 460 | 120 | M8 | R50 ST 450 TFM8 |
| 50 | 1.5 | 500 | 510 | 120 | M8 | R50 ST 500 TFM8 |
| 50 | 1.5 | 550 | 560 | 120 | M8 | R50 ST 550 TFM8 |
| 60 | 2 | 600 | 610 | 120 | M8 | R60 ST 600 TFM8 |
| 60 | 2 | 650 | 660 | 120 | M8 | R60 ST 650 TFM8 |
| 60 | 2 | 700 | 710 | 120 | M8 | R60 ST 700 TFM8 |
| 60 | 2 | 750 | 760 | 120 | M8 | R60 ST 750 TFM8 |
| 60 | 2 | 800 | 810 | 120 | M8 | R60 ST 800 TFM8 |
| 60 | 2 | 850 | 860 | 120 | M8 | R60 ST 850 TFM8 |
| 60 | 2 | 900 | 910 | 100 | M8 | R60 ST 900 TFM8 |
| 60 | 2 | 950 | 960 | 90 | M8 | R60 ST 950 TFM8 |
| 60 | 2 | 1000 | 1010 | 80 | M8 | R60 ST 1000 TFM8 |