



V40Q | SR | PLATE FIXING

BLACK CUSHION RUBBER TYRED WHEEL WITH PRESSED STEEL CENTRE

80, 100, 125




160, 200



| wheel diameter | tread width | fitted height | swivel offset | load capacity | bearing type | swivel | fixed | swivel + total-stop brake |
|----------------|-------------|---------------|---------------|---------------|--------------|------------------|------------------|---------------------------|
| 80 | 25 | 105 | 34 | 50 | roller | V40Q 080 SRR P04 | V41Q 080 SRR P04 | V42Q 080 SRR P04 |
| 100 | 27 | 128 | 34 | 70 | roller | V40Q 100 SRR P04 | V41Q 100 SRR P04 | V42Q 100 SRR P04 |
| 125 | 37 | 155 | 34 | 100 | roller | V40Q 125 SRR P04 | V41Q 125 SRR P04 | V42Q 125 SRR P04 |
| 160 | 38 | 195 | 53 | 135 | roller | V40Q 160 SRR P05 | V41Q 160 SRR P05 | V42Q 160 SRR P05 |
| 200 | 46 | 235 | 53 | 205 | roller | V40Q 200 SRR P05 | V41Q 200 SRR P05 | V42Q 200 SRR P05 |

V40Q | SR | SINGLE HOLE FIXING

BLACK CUSHION RUBBER TYRED WHEEL WITH PRESSED STEEL CENTRE



| wheel diameter | tread width | fitted height | swivel offset | load capacity | bearing type | swivel | fixed | swivel + total-stop brake |
|----------------|-------------|---------------|---------------|---------------|--------------|------------------|-------|---------------------------|
| 80 | 25 | 105 | 34 | 50 | roller | V40Q 080 SRR B12 | | V42Q 080 SRR B12 |
| 100 | 27 | 128 | 34 | 70 | roller | V40Q 100 SRR B12 | | V42Q 100 SRR B12 |
| 125 | 37 | 155 | 34 | 100 | roller | V40Q 125 SRR B12 | | V42Q 125 SRR B12 |
| 160 | 38 | 195 | 53 | 135 | roller | V40Q 160 SRR B12 | | V42Q 160 SRR B12 |
| 200 | 46 | 235 | 53 | 205 | roller | V40Q 200 SRR B12 | | V42Q 200 SRR B12 |



EXPANDING ADAPTOR
for round or square tube

To suit all bolt hole fixing castors

See page 17

i All dimensions are in mm and all loadings are in kg unless otherwise stated