


VSL | AR | PLATE FIXING


BLACK RUBBER TYRED WHEEL WITH ALUMINIUM CENTRE



| wheel diameter | tread width | fitted height | swivel offset | load capacity | bearing type | swivel | fixed | swivel + total-stop brake |
|----------------|-------------|---------------|---------------|---------------|--------------|-----------------|------------------|---------------------------|
| 100 | 35 | 135 | 20 | 160 | ball | VSL 100 ARJ P05 | VSLF 100 ARJ P05 | VSL 100 ARJ P05 SWB |
| 125 | 48 | 159 | 30 | 200 | ball | VSL 125 ARJ P05 | VSLF 125 ARJ P05 | VSL 125 ARJ P05 SWB |
| 150 | 42 | 189 | 39 | 300 | ball | VSL 150 ARJ P05 | VSLF 150 ARJ P05 | VSL 150 ARJ P05 SWB |
| 200 | 37 | 238 | 39.5 | 400 | ball | VSL 200 ARJ P05 | VSLF 200 ARJ P05 | VSL 200 ARJ P05 SWB |

VSL | AP | PLATE FIXING

POLYURETHANE TYRED WHEEL WITH ALUMINIUM CENTRE



| wheel diameter | tread width | fitted height | swivel offset | load capacity | bearing type | swivel | fixed | swivel + total-stop brake |
|----------------|-------------|---------------|---------------|---------------|--------------|-----------------|------------------|---------------------------|
| 100 | 50 | 135 | 20 | 350 | ball | VSL 100 APJ P05 | VSLF 100 APJ P05 | VSL 100 APJ P05 SWB |
| 125 | 50 | 159 | 30 | 450 | ball | VSL 125 APJ P05 | VSLF 125 APJ P05 | VSL 125 APJ P05 SWB |
| 150 | 50 | 189 | 39 | 550 | ball | VSL 150 APJ P05 | VSLF 150 APJ P05 | VSL 150 APJ P05 SWB |
| 200 | 50 | 238 | 39.5 | 600 | ball | VSL 200 APJ P05 | VSLF 200 APJ P05 | VSL 200 APJ P05 SWB |



WHEEL BRAKE
Swivel castors only

Simple side-mounted, foot operated brake acts upon the wheel only

Add **BK** to castor reference



4-WAY DIRECTIONAL LOCK for straight line travel

To suit all swivel castors except with total-stop brake

Add **DL** to castor reference

i All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated