


## VSL | NY | PLATE FIXING


NYLON WHEEL




wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
100	50	135	20	500	ball	VSL 100 NYJHD P05	VSLF 100 NYJHD P05	VSL 100 NYJHD P05 SWB
125	50	159	30	600	ball	VSL 125 NYJHD P05	VSLF 125 NYJHD P05	VSL 125 NYJHD P05 SWB
150	50	189	39	600	ball	VSL 150 NYJHD P05	VSLF 150 NYJHD P05	VSL 150 NYJHD P05 SWB
200	50	238	39.5	800	ball	VSL 200 NYJHD P05	VSLF 200 NYJHD P05	VSL 200 NYJHD P05 SWB

## VSL | NP | PLATE FIXING

GREY POLYURETHANE TYRED WHEEL WITH NYLON CENTRE



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
100	40	135	20	300	ball	VSL 100 NPJ P05	VSLF 100 NPJ P05	VSL 100 NPJ P05 SWB
125	45	159	30	400	ball	VSL 125 NPJ P05	VSLF 125 NPJ P05	VSL 125 NPJ P05 SWB
150	50	189	39	500	ball	VSL 150 NPJ P05	VSLF 150 NPJ P05	VSL 150 NPJ P05 SWB
200	57	238	39.5	600	ball	VSL 200 NPJ P05	VSLF 200 NPJ P05	VSL 200 NPJ P05 SWB



**WHEEL BRAKE**  
Swivel castors only

Simple side-mounted, foot operated brake acts upon the wheel only

Add **BK** to castor reference



**4-WAY DIRECTIONAL LOCK** for straight line travel

To suit all swivel castors except with total-stop brake

Add **DL** to castor reference

**i** All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated